



Flat-Spray-Sprinkler CMD DN15- K80, Type: CMDFP



Technical Specs

Spray characteristics	Flat-Spray-Sprinkler FP, pendent
Responsivity	RTI < 30
Max. working pressure	PS 12.5
Min. working pressure	min. 0.35 bar
Temperature range	68°C, 93°C, 141°C
K- Factor	K 80

Material / Coatings

Sprinklerbody /Deflector	roh = Brass gc = Chrome plated	/ Ral = colour coated
Button	Brass	
Sealing Assembly	Stainless steel / Teflon	
Bulb	Borosilikatglass	
Pins	Stainless steel	

General Instruktionen

Do not install any bulb type sprinkler if the bulb is cracked or is a loss of liquid from the bulb. With the sprinkler held horizontally, a small air bubble should be present. The diameter of the air bubble is approximately 1,6mm for the 57° to 2,4mm for the 182° temperature ratings. A leak-tight ¾ " NPT sprinkler joint should be obtained by applying a minimum to maximum torque of 10 to 14 Nm. Higher levels of torque may distort the sprinkler inlet and cause leakage or impairment of the sprinkler.

Installation Instruction

- Sprinkler may only installed by trained personal.
- Install sprinklers only with the special wrench foreseen for each sprinkler type.
- Install sprinklers only in fully installed and fixed pipe work.
- The threads (fitting / socket) must be clean, free of grease and burrs.

Never install a sprinkler that has had their packaging damaged.

Never install a sprinkler that has been dropped or has suffered any impact.

Always to align sprinklers turn clockwise only. Alignment on the opposite side can create leakage.

Warning

- Sprinklers containing in the original packing have been manufactured and tested according the requirements of the sprinkler authorities.
- Any modification to the sprinkler in the form of painting, warp of deflector, will seriously affect the operation. This will lead to withdraw of insurances approval and any guarantee to JOMOS EuroSprinkler AG
- Sprinklers (brass and chrome plated) may only install in normal atmosphere. For areas with aggressive, corrosive atmosphere ore in case of leakage current, use sprinklers with special coating or stainless steel sprinklers.

Sprinkler marking

RTI- value **Q**= RTI- 035, **S**= RTI- 055, **N**= RTI- 105
 Week of manufacturing **35**= Week 35
 Year of manufacturing **09**= Year 2009
 Temperature range 57°C, **68°C**, 79°C, 93°C, 141°C, 182°C, 260°C
 Sprinkler size **EB**= ½" K- 160, EC= ¾" K- 160
 K- Factor K- 57, K- 80, K- 115, K- 160
 Certificated at **VdS**
 EC-Certificate of Conformity **CE**

